

# EDUTEQ 1500

For solid ceiling or low height installations, the Eduteq provides uniform lighting below and an ambient glow onto the ceiling to reduce glare, ideal for the education sector and 5ft retrofit solutions.



## TECHNICAL INFORMATION

<b>Installation</b>	Surface Mounted (SM)
<b>Body Colour</b>	White (W)
<b>Dimensions</b>	1490mm x 210mm x 68mm
<b>Lumen Output</b>	3000lm (30W), 6000lm (60W) or 8000lm (80W)
<b>Colour Temperature</b>	3000K or 4000K
<b>Colour Rendering Index</b>	CRI80
<b>Optical Distribution</b>	Microprism Diffuser (MP)
<b>Ingress Protection</b>	IP20
<b>Controls</b>	Fixed Output (FO), DALI (DD), PIR Sensor (PIR), Q-Sense (QS) or Casambi (CS)
<b>Emergency</b>	3 Hour Emergency (EM3) or DALI Emergency (EMD)
<b>Accessories</b>	-

## DIMENSIONS



## PRODUCT SHOWCASE



## PRODUCT CODE

**EDU1500/SM/W/3000LM/4000K/80/MP/20/DD**

Eduteq 1500mm, surface mounted, white finish, 3000 lumens, 4000K, CRI80, microprism diffuser, IP20 rated, DALI dimming

SPECIFICATIONS MAY BE ALTERED WITHOUT ADVANCE NOTICE.



Contact us for more information

☎ 020 8687 0190

✉ [sales@edgelighting.co.uk](mailto:sales@edgelighting.co.uk)



**EDGE**  
LIGHTING

[EDGELIGHTING.CO.UK](http://EDGELIGHTING.CO.UK)