

EDGE LIGHTING

LINTEQ 17


Surface mounted linear LED luminaire for continuous or individual installation. Slim profile design ideal allows for shallow installation for discreet lit effect.



TECHNICAL INFORMATION

Installation	Surface Mounted (SM) or Suspended (SS)
Body Colour	Grey (G)
Dimensions	17mm x 7mm x desired length (mm)
Lumen Output (per metre)	500lm (5W), 1000lm (10W), 1500lm (15W) or 2000lm (20W)
Colour Temperature	2700K, 3000K, 4000K, Tuneable White or RGBW
Colour Rendering Index	CRI90
Optical Distribution	Opal Diffuser (OP)
Ingress Protection	IP20
Controls	Fixed Output (FO), DALI (DD), Q-Sense (QS) or Casambi (CS)
Emergency	3 Hour Emergency (EM3) or DALI Emergency (EMD)
Accessories	-

DIMENSIONS



PRODUCT SHOWCASE



PRODUCT CODE

LIN17/SM/G/2000/1000LM/4000K/90/OP/20/FO

Linteq 17, surface mounted, grey finish, 2000mm, 1000 lumens per metre, 4000K, CRI90, opal diffuser, IP20 rated, fixed output

SPECIFICATIONS MAY BE ALTERED WITHOUT ADVANCE NOTICE.



Contact us for more information

☎ 020 8687 0190

✉ sales@edgelighting.co.uk



EDGE
LIGHTING

EDGELIGHTING.CO.UK